

# TH1110DH1003/U

PRO 1000 Horizontal Non-Programmable Thermostats



## Product Info

## Literature

### Product Specifications

Application	1 Heat/1 Cool Conventional Systems and Heat Pumps with No Auxiliary Heat
Dimensions (in.)	3 7/16 in. High x 4 10/16 in. Wide x 1 3/16 in. Deep
Dimensions (mm)	87mm High x 119mm Wide x 30mm Deep
Item Type	Product
Mounting	Horizontal
Electrical Ratings	20 to 30 Vac or 750 mV
Frequency	50 Hz; 60 Hz
Stages	1 Heat/1 Cool
Operating Humidity Range (% RH)	5 to 90% RH, non-condensing
Switch Positions (System)	HEAT-OFF-COOL
Switch Positions (Fan)	AUTO-ON
Power Method	Dual Powered: Battery or Hardwire
Color	Premier White®
Terminal Designations	R, RC, C, W, Y, G, O, B
Display Size	1.32 sq in.
Changeover	Manual
Setting Temperature Range (F)	Heat: 40 F to 90 F; Cool: 50 F to 99 F
Setting Temperature Range (C)	Heat: 4.5 C to 32 C; Cool: 10 C to 37 C
Cycles per Hour	Heating 2 - 6 CPH; Cooling 2 -6 CPH
Cool Current	0.02 A to 1.0 A running
Heat Current	0.02 A to 1.0 A running

