

Model	Volatage	Frequency	Current	Power Input	Speed	Noise	Capacitor	Air Volume	Max.static Pressure	N.W.
	V	Hz	A	W	RPM	dB (A)	uF	m³/h	Pa	Kg
LTF4E-300M-50	220	50	0.4	85	1400	68	3	1700	65	3.6
LTF4E-300M-60	230	60	0.36	80	1700	70	2.5	1785	60	3.6
LTF4D-300M-50	380	50	0.2	70	1400	68	/	1700	65	3.6
LTF4E-300F-50	220	50	0.44	93	1330	60	2.5	2390	60	3.2
LTF4D-300F-50	220	50	0.23	85	1360	60	/	2390	60	3.2
LTF4E-350M-50	220	50	0.78	170	1380	70	6	2935	80	4.6
LTF4E-350M-60	230	60	1.2	250	1600	72	6	3080	82	4.6
LTF4D-350M-50	380	50	0.38	150	1390	72	/	2935	65	4.6
LTF6D-350M-50	380	50	0.28	80	950	58	/	2065	80	4.4
LTF6E-350M-50	220	50	0.4	95	950	58	4	2065	80	4.4
LTF4D-350G-50	400▲	50	0.36	190	1350	70	/	3100	75	6.0
	400Y	50	0.23	131	990	65	/	2600	40	6.0
LTF4E-350G-50	220	50	1.01	216	1400	71	5	3100	60	6.0
LTF6D-350T-50	380	50	0.27	90	920	60	/	1925	70	5.2

LTF6E-350T-50	220	50	0.47	100	900	60	/	1925	70	5.2
LTF4D-400M-50	380	50	0.52	210	1380	72	/	4015	105	5.2
LTF4D-400M-60	400	60	0.6	300	1580	74	/	4215	95	5.2
LTF4E-400M-50	220	50	1.1	235	1320	72	6	4015	105	5.2
LTF4E-400M-60	230	60	1.5	350	1600	74	8	4215	95	5.2
LTF6D-400M-50	380	50	0.35	110	920	62	6	2735	70	5.0
LTF4D-400G-50	400▲	50	0.56	295	1320	72	/	4600	85	6.0
	400Y	50	0.32	179	940	65	/	3500	35	6.0
LTF4E-400G-50	220	50	1.46	325	1390	72	4	4700	75	6.0
LTF6D-400T-50	380	50	0.4	140	915	60	/	3040	70	5.5
LTF6E-400T-50	220	50	0.64	140	900	60	5	3040	70	5.6
LTF4D-400F-50	380	50	0.52	240	1330	68	/	4200	120	6.0
LTF4D-450M-50	380	50	0.7	320	1320	75	/	5890	120	6.8
LTF4D-450M-60	400	60	1.15	580	1400	77	/	6185	110	6.8
LTF4E-450M-50	220	50	2.2	460	1350	75	12	5890	120	6.8

LTF4E-450M-60	230	60	2.3	480	1680	77	12	6185	110	6.8
LTF4E-450G-50	220	50	2.93	640	1320	77	15	7380	100	10.5
LTF4D-450G-50	400▲	50	1.15	567	1370	77	/	7380	115	10.5
	400Y	50	0.73	400	1020	68	/	5700	50	10.5
LTF6E-450G-50	220	50	0.91	198	920	60	6	4800	50	10.2
LTF6D-450G-50	400▲	50	0.45	201	930	60	/	4800	50	10.2
LTF4D-450T-50	380	50	1.45	620	1370	72	/	6705	150	10.0
LTF4D-450F-50	380	50	0.75	350	1320	72	/	5500	100	10.0
LTF4D-500M-50	380	50	1.38	520	1400	78	/	8000	105	10.5
LTF4D-500M-60	400	60	1.45	850	1600	80	/	8400	90	10.5
LTF4E-500M-50	220	50	2.6	560	1360	78	15	8000	105	10.5
LTF4E-500M-60	230	60	3.9	820	1600	80	15	8400	90	10.5
LTF4E-500G-50	220	50	3.67	819	1280	76	15	9000	105	12.8
LTF4D-500G-50	400▲	50	1.59	830	1360	78	/	9000	115	12.8
	400Y	50	0.98	514	1000	72	/	7100	65	12.8
LTF6E-500G-50	220	50	1.34	304	920	68	10	6000	50	12.5

LTF6D-500G-50	400▲	50	0.61	295	900	68	/	6000	60	12.5
LTF4D-500T-50	380	50	1.88	850	1340	74	/	8380	170	10.5
LTF6D-500T-50	380	50	0.85	330	900	68	/	6300	100	10.2
LTF4D-550M-50	380	50	1.26	640	1400	72	/	9260	120	11.0
LTF4D-550M-60	400	60	1.45	850	1600	74	/	9725	110	11.0
LTF4E-550M-50	220	50	2.8	650	1340	72	15	9260	120	11.0
LTF6D-550M-50	380	50	0.58	250	880	62	/	5330	100	10.5
LTF6D-550M-60	400	60	0.7	360	950	64	/	5565	90	10.5
LTF4D-550T-50	380	50	2.45	1100	1360	78	/	10300	150	12.8
LTF6D-550T-50	380	50	0.9	360	890	70	/	6850	90	12.5
LTF4D-550F-50	380	50	1.2	620	1320	72	/	11200	105	12.0
LTF4D-560G-50	400▲	50	2.42	1260	1320	86	/	11800	150	21.0
	400Y	50	1.51	680	920	76	/	8900	70	21.0
LTF6E-560G-50	220	50	2.37	535	920	76	12	7800	75	20.5
LTF6D-560G-50	400▲	50	0.84	440	880	76	/	7800	68	20.5

LTF4D-600M-50	380	50	2.6	750	1400	76	/	10900	115	13.8
LTF6E-600M-60	230	60	2.8	580	1020	64	12	8925	72	13.4
LTF6D-600M-50	380	50	1.35	480	900	62	/	8500	80	13.4
LTF6D-600M-60	400	60	1.4	620	1020	64	/	8925	72	13.4
LTF4D-630M-50	380	50	2.65	1000	1380	78	/	11700	120	15.6
LTF6D-630M-50	380	50	1.48	480	920	68	/	10445	68	15.2
LTF6D-630M-60	400	60	2	880	1000	70	/	10970	70	15.2
LTF4D-630G-50	400▲	50	5.2	2730	1320	83	/	20500	200	33.5
	400Y	50	3.3	1680	1010	78	/	16000	125	33.5
LTF6D-630Q-50	380	50	1.1	400	930	68	/	6500	100	21.5
LTF6D-710M-50	380	50	2.05	920	1020	68	/	10455	95	20.5
LTF6D-710G-50	400▲	50	1.78	925	930	77	/	14800	110	32.0
	400Y	50	1.25	651	720	73	/	12400	65	32.0
LTF8D-710G-50	400▲	50	0.88	450	700	70	/	11200	60	28.5
	400Y	50	0.61	320	530	62	/	9200	10	28.5
LTF6D-800G-50	380	50	4.1	2120	900	80	/	25800	95	35.0
LTF6D-800G-60	380	60	3.5	1938	1070	80	/	25800	125	35.0