

Cross-Flow Type Air Curtain

贯流式风幕机



 Ambient without heating 普通风



Metal casing, compact design.

全金属超薄机身设计。



The air wheel made of high-strength fiberglass plastic material, and the air wheel made of quality aluminum alloy, are especially suitable for the application of heavy oily smoke.

采用玻璃纤维材质的高强度塑料叶轮；另外还有优质铝合金结构叶轮，特别适用于油烟浓度大的地方使用。



Quality motor works for 5000 hours continuously without any defects.

电机持续运行超过5000小时无故障。



Multiple unit specifications: 900mm, 1000mm, 1200mm, 1500mm.

多种机身长度规格：900mm、1000mm、1200mm、1500mm。

Electrical Ratings 技术参数

产品型号 Model No.	规格 Specification (mm)	额定电压/频率/相数 Voltage/ Frequency/ Phase	安装高度 Installation Height (m)	功率 Power(W)		风速 Air Speed (m/s)		风量 Air Volume (m ³ /h)	噪音 Noise (dB)	外型尺寸 Unit Size (mm)	净重 Net Weight (kg)
				低档 Low	高档 High	低档 Low	高档 High				
FM3009-1-S FM3009-1-L	900	220V~ / 50Hz / 1Ph	2.3 ~ 3.0	115	166	9.0	11.0	1220	57	900 × 215 × 200	11.9
FM3010-1-S FM3010-1-L	1000			133	190			1450	58	1000 × 215 × 200	12.9
FM3012-1-S FM3012-1-L	1200			155	209			1710	59	1200 × 215 × 200	15.0
FM3015-1-S FM3015-1-L	1500			202	266			2230	60	1500 × 215 × 200	17.6
FM3009-Y-1-S FM3009-Y-1-L	900			115	166			1220	57	900 × 215 × 200	11.9
FM3010-Y-1-S FM3010-Y-1-L	1000			133	190			1450	58	1000 × 215 × 200	12.9
FM3012-Y-1-S FM3012-Y-1-L	1200			155	209			1710	59	1200 × 215 × 200	15.0
FM3015-Y-1-S FM3015-Y-1-L	1500			202	266			2230	60	1500 × 215 × 200	17.6


Remark: Customized rated voltage and frequency are available.

备注：可根据客户的额定电压和频率来订做合适的产品。

Cross-Flow Type Air Curtain

贯流式风幕机



 Ambient without heating 普通风



Metal casing, strong fire resistance, simple installation and easy cleaning.

全金属外壳，防火性能高，安装方便，容易清洗。



Double air way deflectors' design obtains an even air stream.

采用双导风条设计，出风更平稳。



The air wheel made of high-strength fiberglass plastic material and the air wheel made of quality aluminum alloy, are especially suitable for the application of heavy oily smoke.

采用玻璃纤维材质的高强度塑料叶轮；另外还有优质铝合金结构叶轮，特别适用于油烟浓度大的地方使用。



Quality motor works for 5000 hours continuously without any defects.

电机持续运行超过5000小时无故障。



Multiple unit specifications: 900mm, 1000mm, 1200mm, 1500mm, 1800mm, 2000mm.

多种机身长度规格：900mm、1000mm、1200mm、1500mm、1800mm、2000mm。

Electrical Ratings 技术参数

产品型号 Model No.	规格 Specification (mm)	额定电压/频率/相数 Voltage/ Frequency/ Phase	安装高度 Installation Height (m)	功率 Power(W)		风速 Air Speed (m/s)		风量 Air Volume (m ³ /h)	噪音 Noise (dB)	外型尺寸 Unit Size (mm)	净重 Net Weight (kg)
				低档 Low	高档 High	低档 Low	高档 High				
FM3009-2-S FM3009-2-L	900	220V~ / 50Hz / 1Ph	2.3 ~ 3.0	115	166	9.0	11.0	1220	57	900 × 221 × 183	12.7
FM3010-2-S FM3010-2-L	1000			133	190			1450	58	1000 × 221 × 183	13.5
FM3012-2-S FM3012-2-L	1200			155	209			1710	59	1200 × 221 × 183	16.2
FM3015-2-S FM3015-2-L	1500			202	266			2230	60	1500 × 221 × 183	19.3
FM3018-2-S FM3018-2-L	1800			235	325			2700	62	1800 × 221 × 183	23.0
FM3020-2-S FM3020-2-L	2000			270	380			2900	64	2000 × 221 × 183	27.1
FM3009-Y-2-S FM3009-Y-2-L	900			115	166			1220	57	900 × 221 × 183	12.7
FM3010-Y-2-S FM3010-Y-2-L	1000			133	190			1450	58	1000 × 221 × 183	13.5
FM3012-Y-2-S FM3012-Y-2-L	1200			155	209			1710	59	1200 × 221 × 183	16.2
FM3015-Y-2-S FM3015-Y-2-L	1500			202	266			2230	60	1500 × 221 × 183	19.3
FM3018-Y-2-S FM3018-Y-2-L	1800			235	325			2700	62	1800 × 221 × 183	23.0
FM3020-Y-2-S FM3020-Y-2-L	2000			270	380			2900	64	2000 × 221 × 183	27.1

Remark: Customized rated voltage and frequency are available.

备注：可根据客户的额定电压和频率来订做合适的产品。

Industrial Centrifugal Type Air Curtain 工业离心式风幕机



Ambient without heating 普通风

- Metal casing, strong fire resistance, simple installation and easy cleaning. 全金属外壳, 防火性能高, 安装方便。
- The maximum installation height can reach to 8.0 meters, suitable for factory workshops, warehouse, super markets entrance. 安装高度达到8米, 适合于工厂、大型市场等场所。
- Quality motor runs for 5000 hours continuously without any defects. 电机持续运行超过5000小时无故障。
- Multiple unit specifications: 1000mm, 1200mm, 1500mm 多种机身长度规格: 1000mm、1200mm、1500mm。
- Various installation heights available: 5m, 6m, 7m, 8m. 适用安装高度: 5m、6m、7m、8m。

Electrical Ratings 技术参数

产品型号 Model No.	规格 Specification (mm)	额定电压/频率/相数 Voltage/ Frequency/ Phase	安装高度 Installation Height (m)	功率 Power (W)	每相电流 Amp/Phase (A)	风速 Air Speed (m/s)	风量 Air Volume (m ³ /h)	噪音 Noise (dB)	外型尺寸 Unit Size (mm)	净重 Net Weight (kg)
GFM6010	1000	380V~/50Hz/3Ph	5.0 ~ 6.0	1100	2.55	28.0	3709	64	1000 × 287 × 297	32.7
GFM6012	1200			1100	2.55		3709	66	1200 × 287 × 297	35.6
GFM6015	1500			1850	4.30		5563	68	1500 × 287 × 297	52.0
GFM8010	1000		7.0 ~ 8.0	1500	3.44	30.0	3974	67	1000 × 287 × 297	32.7
GFM8012	1200			1500	3.44		3974	70	1200 × 287 × 297	35.6
GFM8015	1500			2250	5.19		5961	72	1500 × 287 × 297	52.0

Remark: Customized rated voltage and frequency are available.

备注: 可根据客户的额定电压和频率来订做合适的产品。

PTC Air Heater PTC取暖器

新品
NEW



Ambient without heating 普通风
 PTC heater 2kw PTC发热体功率 2kw

- Major applications include bathroom, household and shops. 适用浴室、家庭和小型商场等场所。
- This unit generates high air flow and heating efficiency which saves energy up to 15%. 风量、发热效果好, 比普通取暖器节能15%
- It warms up the occupied room rapidly. 快速将整个空间暖和起来。



Electrical Ratings 技术参数

产品型号 Model No.	规格 Specifications (mm)	额定电压/频率/相数 Voltage/ Frequency/ Phase	安装高度 Installation Height (m)	出风口温度 Outlet Temperature (°C)	风速 Air Speed (m/s)	发热体参数 PTC Heater Parameters		电机功率 Motor Power (W)	风量 Air Volume (m ³ /h)	噪音 Noise (dB)	外形尺寸 Unit Size (mm)	净重 Net Weight (kg)
						发热体功率 PTC Heating Power (W)	每相电流 Amp/Phase (A)					
RM-1006-D-1	600	220V~/50Hz/1Ph	1.8 ~ 2.3	80	4.5	2000	9.5	22	220	42	575 x 148 x 212	3.3

Remark: Customized rated voltage and frequency are available.

备注: 可根据客户的额定电压和频率来订做合适的产品。