## Regulators/Replacement Gauges

## trogen/CO<sub>2</sub> UNIWELD

Regulators for use with Nitrogen or CO2 (with optional F36 adaptor) that have been specially designed for purging and pressure testing.

Large "T" handle with stainless steel pressure adjusting screw and bushing prevent galling.



**RHP800** Nitrogen Regulator

Reseatable Safety Blowoff Opens at 450-475 PSI



Nitrogen Regulator

PSI 800 •1000

G34SD

G8SD

200 psi 400

F36 Adaptor CO<sub>2</sub> Cylinder (CGA320)to Nitrogen (CGA580)

Reseatable

Safety

Blowoff Opens at 850-875 PSI

Part#	UPC#	CGA Inlet	<b>Outlet Connection</b>	Gauges Delivery/Contents	Delivery PSIG
RHP400	13000	580	1⁄4" M.F.	[G8SD] 600/4000 [G7SD]	0-400
RHP500	13100	580	1/4" M.F.	[G8SD] 600/4000 [G7SD]	0-500
RHP800	13800	580	1⁄4" M.F.	[G34SD] 1000/4000 [G7SD]	0-800



2000

	Part#	Pressure	Diam.	Case	N.P.T.
	G34SD	1000 psi	2"	Gold Steel Case	1/4"
Replacement Gauges	G7SD	4000 psi	2"	Gold Steel Case	1/4"
•	G8SD	600 psi	2"	Gold Steel Case	1/4"
					_

NOTE: REPLACEMENT GAUGES DO NOT INCLUDE 2" GAUGE BOOT [SOLD SEPARATELY]

GB20S 2" Gauge Boot Set (2) Black

## Nitrogen and CO2 Regulators

A compact, proven design for soft drink dispensing systems (not beer) and for many types of pressurizing applications. Features include: an adjustable pressure screw with locking nut and a self re-seating relief valve (not designed to protect downstream systems).

	CO₂ Part#	Nitrogen Part#	1½" Gauges/Delivery	Delivery PSIG
Single Gauge	R1346	R1546	60 [G83D]	2-50
Regulator	R1349	R1549	R1549 300 [G84D]	
	CO <sub>2</sub> Part#	Nitrogen Part#	Nitrogen/CO₂ Delivery/Contents	Delivery PSIG
	R1358	R1558	[G20D] 15/4000 [G82D]	2-12
Dual Gauge	*R1360	*R1560	[G83D] 60/4000 [G82D]	2-50
Regulator	*R1362	*R1562	[G78D] 200/4000 [G82D]	5-120
	*R1363	*R1563	[G84D] 300/4000 [G82D]	5-175



boots

## R1563

- CGA320-CO2 inlet connection with 0-ring • CGA580-
- Nitrogen inlet connection
- 1/4" SAE flare outlet
- U.L. Listed

